

## Reliant Pipeline Products

NOM PIPE SIZE (INC)	SLEEVE NUMBER	SLEEVE OD RANGE (IN.)	LAYING LENGTH	WEIGHT	PRICE
---------------------	---------------	-----------------------	---------------	--------	-------

### LINE STOP FITTINGS – SIZES 4”-12” ARE CARBON STEEL

4	RPPCS-0450-44	4.44-4.56	12	85	P.O.A.
	RPPCS-0480-44	4.74-4.86	12		
	RPPCS-0520-44	5.10-5.35	12		
6	RPPCS-0663-66	6.57-6.73	12	120	P.O.A.
	RPPCS-0690-66	6.84-7.10	12		
	RPPCS-0720-66	7.10-7.36	12		
8	RPPCS-0863-88	8.59-8.91	16	175	P.O.A.
	RPPCS-0905-88	8.98-9.30	16		
	RPPCS-0940-88	9.30-9.50	16		
10	RPPCS-1075-1010	10.61-10.86	20	220	P.O.A.
	RPPCS-1110-1010	11.03-11.30	20		
	RPPCS-1200-1010	11.90-12.10	20		
12	RPPCS-1275-1212	12.63-12.88	24	300	P.O.A.
	RPPCS-1320-1212	13.12-13.37	24		
	RPPCS-1420-1212	14.15-14.40	24		

### RPP LINE STOP FITTING MATERIAL SPECIFICATIONS

Line Stop Completion Plug:	Epoxy Coated Ductile Iron
Completion Plug O-Ring:	Buna N
Blind Flange:	3/8” Thick Carbon Steel Epoxy Coated
Blind Flange Gasket:	STANDARD RED RUBBER NITRILE
Valve Flange:	ANSI Class 125 Drilling Epoxy Coated Carbon Steel
Body:	3/8”* Thick Epoxy Coated
Body Gasket:	7/16” Thick Buna N (Nitrile) Outlet Ring Gasket Recessed Into Body Plate
Test Port:	3/4” Iron Pipe Carbon Steel with Stainless Steel Test Plug
Nozzle:	Epoxy Coated Heavy Wall Carbon Steel Outlet Pipe
Rail Hardware:	3/4”* 304 Stainless Steel Bolts with Heavy Hex Nuts and Flat Washers
Mounting Hardware:	Alloy Steel Studs with Heavy Nuts and Flat Washers

- 4-6” NOMINAL BODIES USE .1/4” TOP PLATES, 3/16” BOTTOM PLATES AND 5/8” RAIL HARDWARE