

Reliant Pipeline Products

NOM PIPE SIZE (INC)	SLEEVE NUMBER	SLEEVE OD RANGE (IN.)	LAYING LENGTH	WEIGHT	PRICE
---------------------	---------------	-----------------------	---------------	--------	-------

LINE STOP FITTINGS – SIZES 4”-12” ARE STAINLESS STEEL

4	RPPSS-0450-44	4.46-4.66	15	50	P.O.A.
	RPPSS-0480-44	4.74-5.00	15		
	RPPSS-0520-44	5.10-5.30	15		
6	RPPSS-0663-66	6.59-6.85	15	65	P.O.A.
	RPPSS-0690-66	6.84-7.10	15		
	RPPSS-0720-66	7.10-7.30	15		
8	RPPSS-0863-88	8.62-9.06	20	95	P.O.A.
	RPPSS-0905-88	8.98-9.30	20		
	RPPSS-0940-88	9.20-9.60	20		
10	RPPSS-1075-1010	10.64-10.86	25	185	P.O.A.
	RPPSS-1110-1010	11.03-11.40	25		
	RPPSS-1200-1010	11.85-12.15	25		
12	RPPSS-1275-1212	12.62-12.85	25	265	P.O.A.
	RPPSS-1320-1212	13.12-13.37	25		
	RPPSS-1420-1212	14.10-14.35	25		

RPP LINE STOP FITTING MATERIAL SPECIFICATIONS

Line Stop Completion Plug:	Epoxy Coated Ductile Iron
Completion Plug O-Ring:	Buna N
Blind Flange:	3/8” Thick Carbon Steel Epoxy Coated
Blind Flange Gasket:	Buna N
Valve Flange:	ANSI Class 125 Drilling Epoxy Coated Carbon Steel
Body:	Stainless Steel
Body Gasket:	Full Wrap Buna N with Integral Raised Outlet Seal
Test Port:	3/4” Iron Pipe Carbon Steel with Stainless Steel Test Plug
Nozzle:	Epoxy Coated Heavy Wall Carbon Steel Outlet Pipe
Rail Hardware:	5/8” 304 Stainless Steel Bolts with Heavy Hex Nuts and Flat Washers
Mounting Hardware:	Alloy Steel Studs with Heavy Nuts and Flat Washers